

PRODUCT



Item no.: 003-0230X
+ style code

DESCRIPTION

In 1955 Barba Corsini renovated the loft space within Antonia Gaudí's famous building "La Pedrera" in Barcelona, transforming it from a simple laundry room and storage area into 13 modern duplex apartments. To reinforce the modernist style of the rooms, Corsini decorated the apartment with furniture that he designed himself, including Pedrera lamps and tables. The inspiration for the base of the lights came from the vaulted ceilings of the famous house of "la Pedrera" whilst the cylindrical shape and unique, perforated detail of the chimneys influenced the form of the lampshades.

VERSION - PEDRERA FLOORLAMP Ø39 / PD2

RAL codes are indicative.


- Fabric wire - White:
- Matt white // RAL 9003 // Gloss level 20
- Fabric wire - Black:
- Matt black // RAL 9005 // Gloss level 20

PENDANT VERSION

Order item - look for part number in the pricelist.

Series contains the following:

Pedrera Floorlamp, with dimmer PD2



ACCESSORIES

COLOURS



// Matt black



// Matt white

FACTS

MEASUREMENT - L X W X H MM

Lamp height: 1130 mm
Shade diameter: Ø390 mm
Cable length, exposed: APP. 3000 mm

WEIGHT ITEM - LAMP INCL. WIRE

5700 g

PACKAGING TYPE

Cardboard box

PACKAGING MEASUREMENT - L X W X H CM

L:42 cm X W:42 cm X H:67 cm

WEIGHT PACKAGING - MATERIAL TYPE

- Delivery note: 4 g
- Polystyrene plate bottom: 159 g
- Plastic bags (PE-LD + PO-HD): 60,5 g
- Plastic bags (PE-LD + PO-HD): 32 g
- Plastic bags (PE-LD + PO-HD): 60,5 g
- Cardboard inner: 444 g
- Cardboard: 1580 g
- Polystyrene plate top: 164 g

WEIGHT PACKAGING - TOTAL

8204 g

NUMBER OF PARCELS - SALES PACKAGING

-
ENVIRONMENT

-
TESTS

-
CERTIFICATION AND LABELS

CE - CERTIFIED

1 pcs.

NUMBER OF PARCELS - *TRANSPORT PACKAGING*
1 pcs.

PACKAGING MEASUREMENT - *L X W X H CM*
-

BULB REQUIREMENTS

- Socket: E26 base
- Recommended light source: Halogen light bulb
- Recommended wattage: 70 W
- Max. wattage: 105 W

** Lightbulb not included.*

- *US plug: Type A, 2 PIN, 15 amp, (NEMA 1-15)*
- *US voltage: 120 V*
- *Frequency: 60 Hz*
- *Supply voltage: AC power ~*
- *Normally Closed: IP20*



Class II / Double insulated



CE-Mark



Luminaires accepted for mounting on a flammable base



Mark for Canada and the U.S.